

dual regeneration hose filter for sawdust and cellulose

G&G - JET VAC 150



order number	JET VAC 150
filtration surface	150 m²
air flow	*1 18000 m³/h *2 22500 m³/h *3 27000 m³/h
type of filtering medium	filtrating hose D200
single element surface	1,56 m²
type of regeneration	dual regeneration: JET system + vybratory regeneration
consumption of compressed air	10 Nm3 (6 bar)
number of filtration hoses	96 ks / 96 pcs.
material of filtration hoses	antistatic
disposal of waste	chain conveyor
design for EX	for explosive dust
inlet flange	650x1000 (mm)
output flange	500x1000 (mm)
width - length - height	2232 / 3770 / 5936 (mm)
filter weight	1030 kg
<i>Air flow for different materials</i>	<i>*1 18000 m³/h for fine sawdust from griding</i>
<i>the fan is not included</i>	<i>*2 22500 m³/h for sawdust from chipboards</i>
	<i>*3 27000 m³/h for coarse sawdust from solid wood</i>

Description

The G&G JET VAC (Vacuum Filter for Sawdust and Cellulose dust with Compressed Air Regeneration) is designed mainly for the application of sawdust, textile dust and cellulose dust. The specific feature of the G&G JET VAC filter system is its vacuum design. Which means that the fan is located in the outlet pipeline after the filtration unit. This type of fan has high efficiency. The fan is usually equipped with speed control via a frequency converter depending on how much is a technology used. The standard version of the filter uses textile antistatic hoses with a diameter of 200 mm. The filter hoses are pushed onto the wire baskets. The filtration device is designed for filtration of explosive types of dust. It is equipped with explosion relief membranes to release the pressure outside the filtering device. The filtration device is equipped with a system of regeneration by compressed air pulses and also by a vibratory-regeneration. The standard supply of filter is with a rotary feeder for dust removal. The filtering device can be placed on a supporting steel structure.

Lifespan of filtration medium

The guaranteed service life of the filter hoses is at least 2 to 3 years of filter operation. It is not necessary to clean the filtration medium manually during the operation of the filter unit. We guarantee a long service life of the filtering medium and low replacement costs. The filtering medium consists of a highly mechanically resistant nonwoven fabric in an antistatic design with a surface weight of 500 g/m². The filter hoses with a diameter of 200 mm are placed vertically in the filter unit using wire baskets. The filter regeneration is located on the clean side of the filter at the top of the filter unit.

Applications of filtration device

The G&G JET VAC filter unit is used for the most demanding sawdust and fibre dust extraction applications for operations that operate continuously with a minimum of breaks. Extraction power control is usually applied to the filtering device depending on the machine utilization. The filtering device is regenerated by compressed air pulses during operation, and during a break when the fan is switched off with vibratory-regeneration. The filter is suitable for applications where high filtration equipment performance and stable pressure drop

Working conditions of the filtration unit G&G - JET VAC

The filtration device is designed for filtration of air with the temperature between -30°C and + 80°C in the version without thermal insulation. The filter is designed for explosive dust. Extraction power is determined by the load factor of the filtering surface for each type of dust extracted: Fine wood dust from grinding, sawdust from chipboard machining, sawdust from solid wood machining..

Waste extraction from filtration unit

The waste is removed from the filtration device by a chain conveyor - or a redler. This discharge method avoids the formation of an arch inside the hopper of the filtration device.

